# THE OLD CHAIN OF ROCKS BRIDGE INSPECTION & LOAD RATING



Tom Lohman, PE, SE Horner & Shifrin March 8, 2018














### **CHAIN OF ROCKS**






#### HISTORY TIMELINE






#### HISTORY TIMELINE







# **CONSTRUCTION**






# WATER INTAKE STRUCTURES









### **TOLL BOOTH**






# **ADVERTISEMENT**







# **A DESTINATION**







# **EAGLE DAYS**















- St. Louis 250<sup>th</sup> Birthday
- Movies filmed
- Rte. 66 attraction
  - -International visitors
  - Historic cars
  - Motorcycles

#### **BRIDGE ELEVATION**




PARTIAL ELEVATION



PARTIAL ELEVATION



#### **BRIDGE SECTION**
























#### INSPECTION ACCESS

#### **PROBLEMS**

- Load restriction
- Geometry restriction
- Mississippi River
- Swampy land


#### **SOLUTIONS**

- Towable Manlift
- Suspended Scaffolding
- Tracked Bucket Vehicle












































#### **ACOUSTIC IMAGING**



#### Pier 9 Upstream (North) Face

There is a scour cone at the upstream (north) nose measuring up to 10 ft. deep x 25 ft. radius. The footing / step-out is exposed up to 10 ft. vertically at the upstream (north) face of the pier. The exposed footing / step-out concrete does not exhibit signs of deterioration.

WL Elev. 405.6

Area of local scour

**Channel Bottom** 



### INSPECTION RECORDKEEPING

### **PROBLEMS**


- Note organization
- Pen & paper
- Camera
- Weather


# **SOLUTIONS**


- iPad
- Geographical Information System (GIS)
  - Database






















Span	Truss	Location	Priority	Comment
Spon	11035	COCCOUNT	ritoring	Majority of patches bad between 4 and 0. Same location, 18 inches of deck edge
12	North	Slab	low	bad, 125 sqft total
12	North	Slab	low	Patch at jt 4 sqft
12	North	Slab	low	75sqft bw 10and11 including parts of patches
12	North	Slab	low	Patch just west of 10. 2ft outside delam. 10sqft
12	North	Siab	low	6sqft bw patches bw 7and8
12	North	Slab	low	15 sqft near curb bw 4 end5
12	North	Slab	low	25 sqft bw 6 and 7. Note joint and patches.
17	South	Slab	low	No delaminations or patches between 0 and 4
12	South	Slab	low	40 sf patch west off 11 delaminated
12	South	Slab	medium	20 sf at joint at 6 which is cracked
12	South	Slab	low	5 sf at center bridge
12	South	Slab	low	Expansion joint plate is loose
12	South	Slab	ILW	6 sf 12 ft east of 6 at center bridge
13	North	Slab	low	5 sqft between 7 and 8
13	North	Slah	low	10sqft bw Zand3
13	North	Slab	low	40 sqft bw 8 and 9
13	South	Slab	low	15 sf patch delamination and 4 sf to east of patch
13	South	Slab	low	15 sf patch near 4 and 8 sf delaminated
13	South	Slab	low	40 sf patch near 4 and 8 sr detarminated 40 sf patch delaminated at 6 and cracked
13		Slab	low	40 st patch detarminated at 6 and cracked 20 st between 7&6
13	South	Slab	low	40 sf along gutter between 10 and 11
13	South	Slab	low	5 of between 0 and 1
**				
13	South	Slab	law	20 of between 687
14	North	Slab	low	2.5 ft east side of exp. jt delam. 25sqft total
14	North	Slab	low	3sqft delam at jt
2.7	North	5100	low	Just west of patch at 2, 2sqft delam.
14	South	Slab	low	20 sf at patch and adjacent to patch at 2
14	South	Slab	low	60 sf at 3 and to east, adjacent to patch
14	South	Slab	low	60 sf delamination at 0
	A	# · · ·		Gutter debris build up holding moisture, needs biannual cleaning, typical Illinois
14	South	Slab	low	apPRoach.
				250 sf delaminated between 4 and 8, some very bad. Large patch has cracks and
14	South	Slab	low	discoloration
		71-1-		Patch bw 6 and 5 sounds delam. Also, 2 ft inward entire length of patch delam. 30
15	North	Slab	low	sq ft.
15	North	Slab	low	Several Isqft Delams bw 5 and 0. 15 sqft total.
15	South	Slab	low	8 sf near 2 and at 3
16	North	Slab	low	Just west of pp 7, 10sqsf of slab delaminates 2 ft from curb
16	North	Slab	low	Just east of patch at pp 6, 4 sqft delam.
16	North	Slab	low	Patch at middle of open gate delam. SPReads to next patch east. Abt 100 sqft
16	North	Slab	low	1sqft delam halfway bw 5and 4, 3 ft off curb
16	North	Slab	low	slab repair at exp joint delam. 25 sqft.
16	South	Slab	low	40 sf cracked and delaminated patch at joint
16	South	Slab	low	15 sf bad patch at 2
		Slab drain	high	Clogged with debris, typical many locations
		Bollards	low	Oddly placed
12	North	Curb	low	Curb popping and cracking at jt. Abt 3 ft.
13	North	Curb	low	3ft cracking at 10
All	North and South	Railing	low	Not straight railing allignment
				Clean and seal. PRevious patch across joint has cracked, slab has dropped to west
4		Slab joint @ 6	high	about half inch
5		Slab joint @ 0	high	Clean and seal
5		Slab joint @ 6	high	Clean and seal
- 6		Stab joint @ 6	high	Needs concrete repair, clean and seal
7		Slab joint @ 0	high	Clean and seal
7		Slab joint @ 6	high	Clean and seal. Patch across joint has cracked.
8		Slab joint @ 5	high	Clean and seal. PRevious patch across joint has cracked
- 8		Slab joint @ 10	high	Some concrete cracks. Needs clean and sealed
8		Slab joint @ 15	high	Clean and seal
9		Slab Joint @ 0	high	Clean and seal
9		Slab joint @ 5	high	Gean and seal joint
9		Slabjoint @ 10	high	Clean and seal joint. PRevious patches cast across joint have cracked.
9		Slab joint @ 15	high	Concrete repair, clean and seal
-				and the second s



# LOAD RATING

- No existing load rating
- SAP 2000 2D model
- Gussets
- Pedestrian load rating



# LOAD RATING - KEY ASSUMPTIONS

- AASHTO equations
- Rating factor for allowable people
- 180 pounds per person
- Rated for 50 psf pedestrian load



# LOAD RATING - MODIFIED AASHTO EQ.

Rating Factor = 
$$\frac{\text{Capacity} - 1.3 \text{ (DL)}}{1.3 \text{ Ped}}$$



# LOAD RATING - PEDESTRIAN LOAD




50 psf



100 psf



# LOAD RATING - RESULTS



Note: Truss not shown. Truss width and height vary.



### LOAD RATING - RESULTS

- As-found = 7500 pound personal vehicle
- After repairs = nearly H20 at 15 mph
- Pedestrian = 750 people/span after repairs





# THE OLD CHAIN OF ROCKS BRIDGE INSPECTION & LOAD RATING











