When a Simple Span Bridge Wasn't so Simple

ROUTE 163 OVER BONNE FEMME CREEK

by

JON DERNER, PE, SE ASSISTANT BUSINESS UNIT LEADER, STRUCTURAL

TEAM CONFERENCE - MARCH 2024





AGENDA

- Background
- Project Criteria
 - Hydraulic Design and Bank Stabilization
 - Geotech Investigation
- Construction
 - Cave Portal Discovery
 - Cave Exploration
 - Additional Considerations
 - Scoped Solutions
 - Final Solution
- Conclusions








BACKGROUND


- Originally constructed in 1960's?
- Single span adjacent channel beam founded on closed abutments
- 26' Roadway
- Span is approximately 36'
- Opening is approximately 34' wide and 12' high





BACKGROUND











BACKGROUND











2D HYDRAULICS

 One of our first 2D hydraulics to evaluate flow patterns and establish stream bank velocities to accurately estimate scour and what is required some bank stabilization recommendations.












































STREAM BANK STABILIZATION


- Use of Turf Reinforcement Mat (TRM)
- Protected End Bents with Type 2 Rock Blankets and extended further upstream than typical







8 Initial Borings
































































































Bonne Femme Bridge Cave

Boone County, Missouri BNE149




CAVE SURVEY




Profile View

†N (m)





Surveyed on March 6, 2023 by members of Chouteau Grotto & Cave Research Foundation Kohl Mitchell, Kirsten Alvey-Mudd, Bryn Downes-Ward, Caleb Mundwiller, Diana Dawson



ADDITIONAL CONSIDERATIONS


- Don't block water flow in the cave.
- Minimize depositing material in cave.
- Avoid filling the cave with concrete and minimize water from placement of concrete
- Pink Planarian








SCOPED SOLUTIONS








SCOPED SOLUTIONS








SCOPED SOLUTIONS








		Bent Number						
Турв	Design Data	1	2					
	Pile Type and Size	-	HP 12x53					
	Number 60	-	7					
	Approximate Length Per Each ft	-	18 L+ 35 Cm 38 R+					
Load Bearing Pile	Pile Point Reinforcement ea	-	ALI					
	Min. Galvanized Penetration (Elev.) ft	-	Full Length					
	Pile Driving Verification Method	-	DF					
	Resistance Factor	-	0.40					
	Minimum Nominal Axial Compressive Resistance kip	_	470					
	Foundation Material	Rock	-					
Footing	Minimum Nominal Bearing Resistance Ksf	5.7	-					
	re for piles at Bent No. 2 to elevation 7 h two piles). Elevation 718.2 (middle thr) and Elevation 715.4 (south two piles).	35.3	Beg. Sta. 1					










































									ВІ	LL	OF	R	ΞΙ	NF O	RC :	ING	STEE	ΞL			-c <u>∕</u> î	∑ Ad	ded	ı		
٥.	MAI NO			(E)	NO.	(\$)	28							D	IMENS	IONS	}					NAL	СТН	UAL	LENGTH	WEIGHT
REO'	SIZE	MARK	LOCATION	ХY	SHAPE N	RRUP	SUBSTR. (X)	NO. EACH		В		С		D	E	Ξ.	F		н /		K	NOMINAL	LENGTH	ACTUAL	LEN	WE TONT
 S .	- S	- MA		I EPOXY	-8	I STI	SIS	Ĭ.	FT.	_ IN.	FT.	_ IN.	FT.	. IN.	FT.	_IN.	FT. IN.	FT.	IN.	FT.	IN-	FT.	IN.	F T . I	Ν.	LBS.
			SUBSTRUCTURE			Ц	4	\perp	<u> </u>											_		_			_	
			END BENT NO. 1				\pm	t														F			\dashv	
98	7	Н1	CAVE PLUG	Н	20	Н	+	+	11	8.000								\vdash		\vdash		1	1 8	11	8	2337
80	7	H2	FOOTING	Г	20	\forall	\top	\top	9	8.000										T		_	9 8	9	8	1581
20	7	нз	FOOTING		20	П	\top	\top	39	8.000										\vdash		3	9 8	39	8	1622
4	6	Н4	WALL		20				31	4.000												3	1 4	31	4	188
28	6	Н5	WALL		20				6	8.000													6 8	6	8	280
4	7	Н6	FOOTING		20				28	8.000												2	8 8	28	8	234
						Ц	4	\perp												<u> </u>		_			_	
24	6	UI	CAVE PLUG		10	\rightarrow	4	╄	┞		3	7.000	-	11.000	_					<u> </u>		-	8 1	7	-1	279
29	6	U2	FOOTING	H	10	S	+	+	\vdash		4	1.000	3	5.000	_			-		\vdash		1	1 7	11	3	490
80	7	V1	WALL		19		+	t	8	4.000	1	2.000										F	9 6	9	4	1526
			END BENT NO. 2					Ħ														F				
24	6	Н10	BEAM	$\overline{}$	20	Ц	4	╄	11	0.000										_		-	1 0	11	\rightarrow	397
4	6	H11	BEAM	Ε	20	Н	+	+	41	0.000												4	1 0	41	0	246
11	4	U10	BEAM	Ε	13	s	+	+	3	0.250	2	8.000	3	0.250	2	8.000		\vdash				1	2 2	11	10	87
6	4	U11	BEAM	Ε	10	S	7	F			2	8.000	3	0.250									8 4	8	2	33
\dashv		\dashv	TOTALS - COO1				7	F																	\dashv	
	4			Ε		П	T																			120
	6			L		Ц	\perp	\perp																	_	1237
\longrightarrow	6	_		Ε		Ц	+	\perp	₩									<u> </u>		-		_			\dashv	643
	7	_	7074	H		Н	+	+	-											-		\vdash			\dashv	7300
		\dashv	TOTAL	-		\vdash	+	+	-											\vdash		\vdash			\dashv	8537
		_	TOTAL	Ε	_	\vdash	\pm	1 -	 _ 		_				L			 		 		 _	_	_		763





CONCLUSION









QUESTIONS?



